

### **CONWAY P 50 W**

Flow Rate - (Liters / Hour)	-	50 LPH
Storage Tank - Warm Water	-	22 Liters
No. of Faucets	-	2
Nett Weight in Kg (Approx)	-	25
Number of Power Cord	-	5 Amps 1 number.
Power Supply (AC 50 Hz)	-	180 to 260 Volts
Purification Method	-	Ultraviolet / Ozone
MOC - Housing SS 202	-	Stainless Steel - 0.8 mm Sheet
MOC - Warm Water Tank	-	LLDPE
MOC - Legs SS 202	-	Stainless Steel - 2.0 mm Sheet
MOC - Faucets	-	Brass - Chromium Plated
Dimension of CONWAY 50	-	L 365 x W 355 x H 700 mm

### **CONWAY P 50 WH**

Flow Rate - (Liters / Hour)	-	50 LPH
Storage Tank - Warm Water	-	22 Liters
No. of Faucets	-	2
Nett Weight in Kg (Approx)	-	25
Number of Power Cord	-	5 Amps 1 number.
Power Supply (AC 50 Hz)	-	180 to 260 Volts
Heater Power in Watts	-	500 watts
Purification Method	-	Ultraviolet / Ozone
MOC - Housing SS 202	-	Stainless Steel - 0.8 mm Sheet
MOC - Warm Water Tank	-	LLDPE
MOC - Hot Water Tank SS 304	-	Stainless Steel - 0.8 mm Sheet
MOC - Legs SS 202	-	Stainless Steel - 2.0 mm Sheet
MOC - Faucets	-	Brass - Chromium Plated
Dimension of CONWAY 50	-	L 365 x W 355 x H 700 mm