

CONWAY P 100 NH
CONTACTLESS - IR SENSOR BASED



TECHNICAL SPECIFICATION

MODEL : CONWAY - P 100 NH - IR SENSOR

Storage Tank - Normal Water	50 Liters
Storage Tank - Hot Water	4 Liters
No. of Faucets	2
Net Weight in Kg (Approx.)	40 Kgs
Purification Method	UV + Ozone
Number of Power Cord	15 Amps 1 number.
Power Supply (AC 50 Hz)	180 to 260 Volts
Heater Power in Watts	1000 watts
MOC - Housing SS 304	Stainless Steel - 0.8 mm Sheet
MOC - Normal Water Tank	LLDPE
MOC - Hot Water Tank SS 304	Stainless Steel - 0.8 mm Sheet
MOC - Rear cover SS 202	Stainless Steel - 0.8 mm Sheet
MOC - Legs SS 202	Stainless Steel - 2.0 mm Sheet
MOC - Faucets	Brass - Chromium Plated
Dimension of CONWAY 100	L 455 x W 450 x H 1370 mm
Filtration Technique	Spun Candle and Carbon Block.
Water Control	Solenoid Valve MCN22 (SS 304)
Sensor	Infrared M18 (NPN)
PCB	Micro Controlled Based