

CONWAY P 125 NC
CONTACTLESS - IR SENSOR BASED



TECHNICAL SPECIFICATION

MODEL : CONWAY - P 125 NC – IR Sensor

Flow Rate - (Liters / Hour)	125 LPH
Storage Tank - Normal Water	30 Liters
Storage Tank - Cold Water	40 Liters
No. of Faucets	2
Net Weight in Kg (Approx.)	66
Purification Method	UV + Ozone
MOC - Housing SS 304	Stainless Steel - 0.8 mm Sheet
MOC - Normal Water Tank	LLDPE
MOC – Hot Water Tank SS 304	Stainless Steel - 0.8 mm Sheet
MOC – Rear cover SS 202	Stainless Steel - 0.8 mm Sheet
MOC - Legs SS 202	Stainless Steel - 2.0 mm Sheet
MOC – Faucets	Brass - Chromium Plated
Insulation of Cooling Tank	PUF – EPE
Dimension of CONWAY 75	L 550 x W 525 x H 1450 mm
Compressor Make	Emerson
Compressor Refrigerant	R – 134a
Filtration Technique	Spun Candle and Carbon Block
Water Control	Solenoid Valve MCN22 (SS 304)
Sensor	Infrared M18 (NPN)
PCB	Micro Controlled Based