

**CONWAY P 125 NH**  
**CONTACTLESS - IR SENSOR BASED**



## TECHNICAL SPECIFICATION

**MODEL : CONWAY - P 125 NH - IR Sensor**

<b>Flow Rate - (Liters / Hour)</b>	<b>125 LPH</b>
<b>Storage Tank - Normal Water</b>	<b>80 Liters</b>
<b>Storage Tank - Hot Water</b>	<b>5 Liters</b>
<b>No. of Faucets</b>	<b>2</b>
<b>Net Weight in Kg (Approx.)</b>	<b>69</b>
<b>Purification Method</b>	<b>UV + Ozone</b>
<b>Number of Power Cord</b>	<b>15 Amps 1 number.</b>
<b>Power Supply (AC 50 Hz)</b>	<b>180 to 260 Volts</b>
<b>Heater Power in Watts</b>	<b>1000 watts</b>
<b>MOC - Housing SS 304</b>	<b>Stainless Steel - 0.8 mm Sheet</b>
<b>MOC - Normal Water Tank</b>	<b>LLDPE</b>
<b>MOC - Hot Water Tank SS 304</b>	<b>Stainless Steel - 0.8 mm Sheet</b>
<b>MOC - Rear cover SS 202</b>	<b>Stainless Steel - 0.8 mm Sheet</b>
<b>MOC - Legs SS 202</b>	<b>Stainless Steel - 2.0 mm Sheet</b>
<b>MOC - Faucets</b>	<b>Brass - Chromium Plated</b>
<b>Dimension of CONWAY 75</b>	<b>L 550 x W 525 x H 1450 mm</b>
<b>Filtration Technique</b>	<b>Spun Candle and Carbon Block</b>
<b>Water Control</b>	<b>Solenoid Valve MCN22 (SS 304 )</b>
<b>Sensor</b>	<b>Infrared M18 (NPN)</b>
<b>PCB</b>	<b>Micro Controlled Based</b>