

CONWAY P 125 NHC
CONTACTLESS - IR SENSOR BASED



TECHNICAL SPECIFICATION

MODEL : CONWAY - P 125 NHC - IR Sensor

Flow Rate - (Liters / Hour)	125 LPH
Storage Tank - Normal Water	30 Liters
Storage Tank - Cold Water	40 Liters
Storage Tank - Hot Water	5 Liters
No. of Faucets	3
Net Weight in Kg (Approx.)	69
Purification Method	UV + Ozone
Number of Power Cord	15 Amps 1 number.
Power Supply (AC 50 Hz)	180 to 260 Volts
Heater Power in Watts	1000 watts
MOC - Housing SS 304	Stainless Steel - 0.8 mm Sheet
MOC - Normal Water Tank	LLDPE
MOC - Hot & Cold Water Tank SS 304	Stainless Steel - 0.8 mm Sheet
MOC - Rear cover SS 202	Stainless Steel - 0.8 mm Sheet
MOC - Legs SS 202	Stainless Steel - 2.0 mm Sheet
MOC - Faucets	Brass - Chromium Plated
Insulation of Cooling Tank	PUF - EPE
Dimension of CONWAY 75	L 550 x W 525 x H 1450 mm
Compressor Make	Emerson
Compressor Refrigerant	R - 134a
Filtration Technique	Spun Candle and Carbon Block
Water Control	Solenoid Valve MCN22 (SS 304)
Sensor	Infrared M18 (NPN)
PCB	Micro Controlled Based