

CONWAY P 125 NHC CONTACTLESS - PEDAL OPERATED BASED



TECHNICAL SPECIFICATION

MODEL: CONWAY - P 125 NHC - Pedal Operated

	· · · · · · · · · · · · · · · · · · ·
Operating Method	Pedal Type
Flow Rate - (Liters / Hour)	100 LPH
Storage Tank - Normal Water	30 Liters
Storage Tank - Cold Water	40 Liters
Storage Tank - Hot Water	5 Liters
No. of Faucets	3
Net Weight in Kg (Approx.)	69
Purification Method	UV + OZONE
Number of Power Cord	15 Amps 1 number.
Heater Power in Watts	1000 watts
Power Supply (AC 50 Hz)	180 to 260 Volts
MOC - Housing SS 304	Stainless Steel - 0.8 mm Sheet
MOC - Normal Water Tank	LLDPE
MOC – Hot & Cold Water Tank SS 304	Stainless Steel - 0.8 mm Sheet
MOC – Rear cover SS 202	Stainless Steel - 0.8 mm Sheet
MOC - Legs SS 202	Stainless Steel - 2.0 mm Sheet
MOC - Faucets	Brass - Chromium Plated
Insulation of Cooling Tank	Poly Urethane foam
Compressor Make	Emerson
Compressor Refrigerant	R – 134a
Dimension of CONWAY 125	L 550 x W 525 x H 1450 mm
Filtration Technique	Spun Candle and Carbon Block.

