



# CONWAY P 125 NN

## CONTACTLESS - PEDAL OPERATED BASED





## TECHNICAL SPECIFICATION

MODEL : CONWAY - P 125 NN - Pedal Operated

|                                    |                                       |
|------------------------------------|---------------------------------------|
| <b>Operating Method</b>            | <b>Pedal Type</b>                     |
| <b>Flow Rate - (Liters / Hour)</b> | <b>100 LPH</b>                        |
| <b>Storage Tank - Normal Water</b> | <b>80 Liters</b>                      |
| <b>No. of Faucets</b>              | <b>2</b>                              |
| <b>Net Weight in Kg (Approx.)</b>  | <b>48</b>                             |
| <b>Number of Power Cord</b>        | <b>5 Amps 1 Number</b>                |
| <b>Purification Method</b>         | <b>UV + OZONE</b>                     |
| <b>MOC - Housing SS 304</b>        | <b>Stainless Steel - 0.8 mm Sheet</b> |
| <b>MOC - Normal Water Tank</b>     | <b>LLDPE</b>                          |
| <b>MOC - Rear cover SS 202</b>     | <b>Stainless Steel - 0.8 mm Sheet</b> |
| <b>MOC - Legs SS 202</b>           | <b>Stainless Steel - 2.0 mm Sheet</b> |
| <b>MOC - Faucets</b>               | <b>Brass - Chromium Plated</b>        |
| <b>Dimension of CONWAY 125</b>     | <b>L 550 x W 525 x H 1450 mm</b>      |
| <b>Filtration Technique</b>        | <b>Spun Candle and Carbon Block.</b>  |