

TECHNICAL SPECIFICATION

Model : CONWAY RO + UV 10 DLX

Material of Construction	SS 304
Storage Tank - Normal Water	SS tank - 8 Liters
Purification Stages	Sediment Filter, Pre Carbon Filter, Post Carbon Filter, Membrane
Purification Technology	Reverse Osmosis System + UV
PCB	Micro Controller based PCB
Product Dimension	L 370 X W 195 X H 525
Weight	14 Kg
Inlet Pressure	Min 0.6 to 1 kg/sq.cm
Inlet water Temperature	25 to 40 Celsius
Inlet Power Supply	Single Phase 230 V/AC, 50 Hz
Membranes	75 GPD
HP Pump	150 GPD
Filters	Spun, Activated Carbon, Post carbon
UV Lamp	8 Watts
Installation Type	Wall Mounting
Power Consumption	40 Watts
Packing	Carton Box with EPE foam
<u>Unique Features:</u>	<ul style="list-style-type: none"> • SS304 grade Stainless Steel Housing, Tank and Frame. • Fully Automatic Micro Controller based PCB with SMPS. • SS Probe based water level controller. • LED indicators for easy understanding of functionality. • Inlet and outlet at the bottom for easy convenience. • Enhanced Life of the product, hence value for money. • Aesthetically designed to suit any kitchen Interior. • Anti-corrosive, easy maintenance and undiminished resale value.