

## TECHNICAL SPECIFICATION

Model : CONWAY UV DLX

<b>Material of Construction</b>	SS 304
<b>Storage Tank - Normal Water</b>	SS tank - 8 Liters
<b>Purification Stages</b>	Sediment Filter, Pre Carbon Filter, Post Carbon Filter
<b>Purification Technology</b>	Ultraviolet
<b>PCB</b>	Micro Controller based PCB
<b>Product Dimension</b>	L 370 X W 195 X H 525
<b>Weight</b>	11 Kg
<b>Inlet Pressure</b>	Min 0.6 to 1 kg/sq.cm
<b>Inlet water Temperature</b>	25 to 40 Celsius
<b>Inlet Power Supply</b>	Single Phase 230 V/AC, 50 Hz
<b>UV Lamp</b>	11 Watts
<b>Life of UV Lamp</b>	3000 hours @ standard operating conditions
<b>Installation Type</b>	Wall Mounting
<b>Power Consumption</b>	40 Watts
<b>Packing</b>	Carton Box with EPE foam
<b><u>Unique Features:</u></b>	<ul style="list-style-type: none"><li>• SS304 grade Stainless Steel Housing, Tank and Frame.</li><li>• Fully Automatic Micro Controller based PCB with SMPS.</li><li>• SS Probe based water level controller.</li><li>• LED indicators for easy understanding of functionality.</li><li>• Inlet and outlet at the bottom for easy convenience.</li><li>• Enhanced Life of the product, hence value for money.</li><li>• Aesthetically designed to suit any kitchen Interior.</li><li>• Anti-corrosive, easy maintenance and undiminished resale value.</li><li>• Unique design makes it easily serviceable.</li></ul>